



Digital crane scale

Model: OCS-SP




Features

- ◆ **Enclosure:**
NEMA 12/IP54 powder coated Die-Casting Aluminum, very light, easy to bring.
- ◆ **Multi-weighing units:**
Kg, lb, N are selectable, kg are default unit.
- ◆ **Multi-function operation:**
Tare, Zero, Auto zero tracking, Total, Hold, Overload warning and record, operated through infrared remote controller.
- ◆ **User-friendly design:**
Large red 5 digit LED display (digit height 30mm), Battery Operated with low battery indication, Automatic turn off , power-saving function.
- ◆ **Gravity regulation:**
The acceleration of gravity can be regulated through remote controller according to different places value.
- ◆ **Multi options:**
RS-232-continuous or on demand data output, user-selectable.

Main technical data

Accuracy Standard	According to OIML class III
Display	30mm (1.2") 5digits LCD/LED
Filtering	Low,Medium or High selectable
Units	Kilograms , Pounds or Newtons selectable
Resolution	2000 to 3000 divisions standard up to 15,000 available
Zero Range	4% F.S.
Tare Range	100% F.S.
Overload Indication	100% F.S. + 9e
Max. Safety Load	125% F.S.
Ultimate Load	400% F.S.
Battery Type	Fully sealed Lead-Acid battery, 6V/5Ah
Battery Life	≥60 hours
Adapter	DC 9V/1000mA
Operating Temperature Range	- 20C ~ + 50 C
Operating Humidity	≤85% RH under 20 C
Remote Controller Distance	Max. 15m
Battery of Remote Controller	AAA battery, 1.5V x2
Acceleration of Gravity	9.793,Can be regulated



Dimensions and Specifications

MODEL	Cap.(kg)	Resolution (kg)	A(mm)	C(mm)	H(mm)	N.W(kg)	G.W.(kg)
OCS-SP-005	50	0.02	34	25	370	4	5
OCS-SP-01	100	0.05	34	25	370	4	5
OCS-SP-02	200	0.1	34	25	370	4	5
OCS-SP-03	300	0.1	34	25	370	4	5
OCS-SP-05	500	0.2	42	27	390	4.5	5.5
OCS-SP-1	1000	0.5	42	27	390	4.5	5.5